

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1-11. (Canceled)

12. (Currently Amended) An apparatus, comprising:

a capture mechanism configured to engage a peripheral device, the capture mechanism having a grasping member and an actuator, the actuator being configured to actuate the grasping member to close the grasping member around the peripheral device to engage the peripheral device therein in response to ~~a movement~~ of the peripheral device being inserted into the grasping member; ~~a coupling mechanism being configured to move in response to the movement of the peripheral device when the peripheral device is engaged by the capture mechanism~~; and

a sensing assembly configured to detect ~~a manipulation~~ movement of the peripheral device while the peripheral device is engaged by the capture mechanism.

13. (Previously presented) The apparatus of claim 12, wherein the grasping member has a tubular shape.

14. (Previously presented) The apparatus of claim 12, the grasping member being a tubular grasping member, wherein the actuator further includes:

a spring configured to elongate and compress the tubular grasping member in response to movement of the peripheral device such that the cross-sectional dimension of the tubular grasping member is adjusted.

15. (Previously presented) The apparatus of claim 12, the grasping member being a tubular grasping member, wherein the grasping member further includes:

a spring configured to elongate and compress the tubular grasping member in response to movement of the peripheral device such that the cross-sectional dimension of the tubular grasping member is adjusted, the grasping member being configured to engage the peripheral device in response to the elongation of the tubular member and being configured to release the peripheral device in response to the compression of the tubular member.

16. (Previously presented) The apparatus of claim 12, wherein the capture mechanism is disposed within the sensing assembly.

17. (Previously presented) The apparatus of claim 16, wherein the capture mechanism further includes:

a plurality of jaws configured to surround and engage the peripheral device.

18. (Currently Amended) An apparatus comprising:

a capture mechanism configured to engage a peripheral device, the capture mechanism having a grasping member and an actuator, the actuator being configured to automatically actuate

the grasping member to close the grasping member around the peripheral device to engage the peripheral device therein in response to ~~a movement of the peripheral device being inserted into the grasping member~~; ~~a coupling mechanism being configured to move in response to the movement of the peripheral device when the peripheral device is engaged by the capture mechanism~~;

a sensing assembly configured to detect a manipulation of the peripheral device while the peripheral device is engaged by the capture mechanism;

wherein the capture mechanism has a plurality of jaws; and wherein the actuator further includes:

a spring configured to bias the plurality of jaws in a closed position, at least a portion of the grasping member being disposed within the spring; and

a semi-conical expander disposed proximate to the spring and configured to manipulate the plurality of jaws between the closed position and an open position; ~~and~~

~~an actuator disposed proximate and being coupled to the semi-conical expander.~~

19. (Previously presented) The apparatus of claim 12, wherein the capture mechanism has a plurality of jaws; and wherein the capture mechanism further includes:

an automatic capture-and-release mechanism configured to automatically actuate the plurality of jaws to engage the peripheral device.

20. (Previously presented) The apparatus of claim 12, wherein the capture mechanism has a plurality of jaws, the plurality of jaws of the capture mechanism are actuated by a force applied by a lever associated with a movement of the peripheral device.

21-33. (Canceled)

34. (Currently Amended) A method for simulating a medical procedure in a medical procedure simulation system, the method comprising:

receiving a peripheral device configured as a medical instrument into a capture mechanism, the capture mechanism being configured to engage the peripheral device;

automatically engaging the peripheral device in a grasping member of the capture mechanism based on a first movement of the peripheral device, wherein the grasping member allows the peripheral device to be inserted therein and automatically closes around the peripheral device to engage the peripheral device from the first movement; and

automatically releasing the peripheral device from the grasping member based on a second movement of the peripheral device, wherein the grasping member automatically opens in response to the second movement to allow the peripheral device to be released therefrom.

35. (Previously presented) The method of claim 34, wherein the automatically engaging the peripheral device further includes providing frictionally engagement to the peripheral device.

36. (Previously presented) The method of claim 34, wherein the automatically engaging the peripheral device further includes providing a plurality of jaws to engage the peripheral device.
37. (Previously presented) The method of claim 36, wherein the providing a plurality of jaws further includes moving a lever to control the plurality of jaws.
38. (Previously presented) The method of claim 34, wherein the automatically engaging the peripheral device includes mechanically actuating a lever to open and close a plurality of jaws.
39. (Previously presented) The method of claim 34, wherein the automatically engaging the peripheral device further includes:
- inserting the peripheral device into a tubular member having cross-sectional dimension;
 - moving a spring from a first position to a second position, wherein the second position is different from the first position;
 - reducing the cross-sectional dimension of the tubular member based on the movement of the spring; and
 - frictionally engaging the peripheral device with the tubular member while the cross-sectional dimension is reduced.
40. (Previously presented) The method of claim 34, further comprising:
- inserting the peripheral device into a tubular member having cross-sectional dimension;

moving a spring from a first position to a second position, wherein the second position is different from the first position;

reducing the cross-sectional dimension of the tubular member based on the movement of the spring;

frictionally engaging the peripheral device with the tubular member while the cross-sectional dimension is reduced; and

releasing the peripheral device by increasing the cross-sectional dimension of the tubular member based on the movement of the spring from the second position to the first position.

Claims 41-44 (Cancelled)